



JM01

GPS Vehicle Tracker



Vehicle battery protection

Never drain out of the battery of motorcycle for optimal protection



IP65 dust and water proof

Water-resistant to ensure stable operation in tough environment



Remote cut-off (petrol/power)

Compel the vehicle to stop by breaking off the fuel connection



9-90V voltage range

Wide operating voltage applicable to all types of vehicles



SOS button (optional)

Thumb sized button allowing urgent call during an emergency case



Multiple alarms

Instant alert for vibration, overspeed, power off, geo-fence



Configurable tracking modes

Location uploaded following fixed distance, time interval, preset cornering



Tracked by: SMS, APP, Web

Report location in real time through different interfaces

Application



Yacht



Vehicle tracking



Motorcycle

GSM Specification

GSM frequency	850/900/1800/1900 MHz
GPRS	Class 12, TCP/IP
Memory	32+32Mb
Phase error	RMSPE<5,PPE<20
Max output	GSM850/GSM900:33±3dBm GSM1800/GSM1900:30±3dBm
Max frequency error	±0.1ppm

GPS Specification

GPS chipset	MTK high sensitivity chip
Frequency	L1, 1575.42MHz C/A code
GPS channel	66
Location accuracy	<10 meters
Tracking sensitivity	-165dBm
Acquisition sensitivity	-148dBm
TTF (open sky)	Avg. hot start ≤1sec Avg. cold start ≤35sec

Function & Package

Dust-waterproof level	IP65
Battery	800mAh/3.7V Li-Polymer battery
Working voltage/current	9-90VDC/7mA(60VDC)
Standby time	55 hours
Working time	4 hours
Operating temperature	-20℃~70℃
Device weight	82g
Device dimension	87.0(L)*74.0(W)*18.7(H)mm
Box weight	266g (without SOS cable)
Box dimension	128(L)*110(W)*56(H)mm

Contact

Jimi Electronic Co., Ltd
Shenzhen Concox Information Technology Co., Ltd

Add: 4/F, Building B, Gaoxinqi Industrial Park, Liuxian 1st Road, No.67 Bao'an District, Shenzhen

Tel: +86 755 6664 2520

Web: www.iconcox.com www.jimilab.com

Email: info@concox.cn info@jimilab.com